VACUFLEX® VSM-L-SO2

Very lightweight, smooth-bore, solid-wall plastic hose with very low flow resistance



Applications extraction systems, vacuum cleaner, industrial vacuum cleaners, cable protection, exhaust gas extraction

Structure TPO, black / jet black (similar RAL 9005), opaque, profile helix / solid profile helix

Temperature -50°C up to 60°C

Properties excellent flexibility, corrugated outside, smooth inside, crush-resistant, good resistance to compressed air containing mineral oil, good oil & petrol resistance, hydrolysis & microbe resistant, weather proof, good ozone- & UV-resistance, rot proof





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
27	34,00	45	0,50	0,50	0,15500	4-2206-027-00
29	36,00	45	0,50	0,50	0,16500	4-2206-029-00
32	39,00	50	0,45	0,45	0,18500	4-2206-032-00
38	45,00	55	0,35	0,35	0,22000	4-2206-038-00
50	58,00	75	0,20	0,20	0,28950	4-2206-050-00

Ocono VACUFLEX GmbH | Hessenring 8-12 | 64546 Mörfelden-Walldorf | Germany | T +49 6105 93390 | vacuflex@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026