VACUFLEX® VC2 PU AGRI MHR

Lightweight, highly flexible and UV-resistant polyether-polyurethane hose, reinforced with an impact-resistant rigid PVC spiral



Applications waste water, irrigation, liquid manure spreading, agriculture

Structure Polyether-Polyurethane, green, translucent, plastic spiral / rigid PVC

Temperature -40°C up to 80°C

Properties excellent flexibility, good low-temperature flexibility, good abrasion resistance, corrugated outside smooth inside, hydrolysis & microbe resistant rot proof weather proof good ozone- & UV-resistance





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
40	47,30	0,70	1,20	0,70	11,40	30	3-79B8-040-30/998
51	58,50	0,75	1,00	0,60	13,80	30	3-79B8-051-30/998

Ocono VACUFLEX GmbH | Hessenring 8-12 | 64546 Mörfelden-Walldorf | Germany | T +49 6105 93390 | vacuflex@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026