

### VC2 SeedX PU

A lightweight, highly flexible and UV-resistant polyether-polyurethane hose, reinforced with an impact-resistant rigid PVC spiral

|                     |                                                                                                                                                                                    |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Applications</b> | seed conveying, agriculture, waste water, irrigation, air supply                                                                                                                   |
| <b>Structure</b>    | Polyether-Polyurethane, uncolored, transparent, plastic spiral / rigid PVC                                                                                                         |
| <b>Temperature</b>  | -30°C up to 90°C                                                                                                                                                                   |
| <b>Properties</b>   | very good flexibility, , good abrasion resistance, corrugated outside<br>very smooth inside, good ozone- & UV-resistance hydrolysis & microbe<br>resistant rot proof weather proof |



| Inner Diameter (mm) | Wall Thickness (mm) | Max. Operating Pressure (bar) | Vacuum Max. (bar) | Weight (kg/m) | Article Number |
|---------------------|---------------------|-------------------------------|-------------------|---------------|----------------|
| 32                  | 0,60                | 2,50                          | 0,65              | 0,27000       | 3-6800-032-01  |
| 35                  | 0,60                | 2,50                          | 0,65              | 0,27800       | 3-6800-035-01  |
| 40                  | 0,60                | 2,50                          | 0,60              | 0,31800       | 3-6800-040-01  |
| 45                  | 0,60                | 2,50                          | 0,60              | 0,37100       | 3-6800-045-01  |