

VACUFLEX® VC2 TPR

Light weight and highly flexible hose made of TPR, crush resistant

- Applications** automotive engineering, vehicle construction, air conditioning & HVAC, steam extraction, ventilation
- Structure** TPR, black / jet black (similar RAL 9005), opaque, plastic spiral / PP
- Temperature** -40°C up to 100°C
- Properties** light weight, good flexibility, good chemical resistance, corrugated outside, very smooth inside, good ozone- & UV-resistance, hydrolysis & microbe resistant, rot proof, weather proof



Inner Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
8	8	2,50	0,75	0,04500	3-6506-008-00/999
8,3	8	2,50	0,75	0,02200	3-6506-008-30
10	10	2,50	0,75	0,05500	3-6506-010-00/999
12	12	2,50	0,75	0,06900	3-6506-012-00/999
14	14	2,50	0,75	0,07400	3-6506-014-00/999
16	16	2,50	0,75	0,08600	3-6506-016-00/999
18	18	2,50	0,75	0,09800	3-6506-018-00/999
20	20	2,50	0,75	0,11000	3-6506-020-00/999
22	22	2,50	0,75	0,12500	3-6506-022-00/999
25	25	2,00	0,55	0,14200	3-6506-025-00/999
26	26	2,00	0,55	0,15900	3-6506-026-00/999
27	27	2,00	0,55	0,18400	3-6506-027-00
30	30	2,00	0,55	0,17300	3-6506-030-00/999
32	32	2,00	0,55	0,18000	3-6506-032-00/999
35	35	2,00	0,55	0,19700	3-6506-035-00/999
38	38	1,50	0,45	0,21200	3-6506-038-00/999
40	40	1,50	0,45	0,22500	3-6506-040-00/999
42	42	1,50	0,45	0,23700	3-6506-042-00/999