VACUFLEX® K1H PVC FR

Light weight and flexible hose made of PVC, flame resistant

Applications	extraction systems, air supply, cable protection, dust extraction, ventilation
Structure	PVC, grey, opaque, steel wire / spring steel wire / coated / PVC
Temperature	-10°C up to 70°C
Properties	light weight, good flexibility, good chemical resistance, hydrolysis & microbe resistant,







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
50	55,40	0,75	50	0,40	0,25	0,47100	1-24DG-050-00/998
100	106,60	0,75	100	0,40	0,25	0,87300	1-24DG-100-00/998
110	116,60	0,75	130	0,40	0,25	0,96030	1-24DG-110-00/998
120	126,60	0,75	180	0,40	0,25	1,07200	1-24DG-120-00/998
140	147,60	0,75	185	0,20	0,12	1,37500	1-24DG-140-00/998
150	167,60	0,75	190	0,20	0,12	1,47500	1-24DG-150-00/998
200	207,60	0,75	250	0,10	0,05	1,94500	1-24DG-200-00/998
250	257,60	0,75	330	0,10	0,03	2,43100	1-24DG-250-00/998
300	307,60	0,75	400		0,03	2,91700	1-24DG-300-00/998

Ocono VACUFLEX GmbH | Hessenring 8-12 | 64546 Mörfelden-Walldorf | Germany | T +49 6105 93390 | vacuflex@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 23.11.2026