TWINFLEXX PU (OVAL)

Durable and flexible, double-walled TPU hose with an integrated PVC inner hose for steam cleaners and spray-extraction machines

Applications cleaning, steam extraction, industrial vacuum cleaners, sprayers

Structure Polyether-Polyurethane, black / jet black (similar RAL 9005), opaque, steel wire / spring steel wire / coated / PU

Temperature -40°C up to 90°C, short term up to 125°C

Properties very good flexibility, good low-temperature flexibility, very good abrasion resistance, very smooth inside, hydrolysis & microbe resistant, flex fatigue resistance > 200,000 cycles, flexibility factor min. 0.25

Optional max. production length: 16 m; also available with a round, smooth-walled hose







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
31	37,50	1,50	1,50	3,50	0,60	0,39600	5-9106-031-00
32	38,80	1,50	1,50	3,50	0,60	0,39600	5-9206-032-00

Ocono VACUFLEX GmbH | Hessenring 8-12 | 64546 Mörfelden-Walldorf | Germany | T +49 6105 93390 | vacuflex@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 23.11.2026