

VACUFLEX® KA-GH PU MHR

Double-walled, flexible polyurethane hose

Applications	dental technology, cable protection, medical devices
Structure	TPU / Polyether-Polyurethane, grey / light grey (similar RAL 7035), opaque, plastic spiral / rigid PVC
Temperature	-10°C up to 60°C
Properties	light weight, excellent flexibility, smooth outside, very smooth inside, hydrolysis & microbe resistant, rot proof, weather proof



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
8	12,00	2,00	10	0,03	0,30	0,09300	2-8808-008-00
10	14,00	2,00	12	0,09	0,29	0,12400	2-8808-010-00
11	15,00	2,00	13	0,09	0,29	0,12500	2-8808-011-00
13	17,00	2,00	13	0,09	0,28	0,16500	2-8808-013-00
15	19,00	2,00	13	0,10	0,27	0,13800	2-8808-015-00
16	20,00	2,00	20	0,12	0,26	0,14700	2-8808-016-00
17	21,00	2,00	21	0,13	0,25	0,15400	2-8808-017-00
20	25,00	2,00	21	0,14	0,23	0,18300	2-8808-020-00
25	30,00	2,50	23	0,19	0,20	0,22900	2-8808-025-00