


VACUFLEX® VSM-L-SO2

Very lightweight, smooth-bore, solid-wall plastic hose with very low flow resistance

- Applications** extraction systems, vacuum cleaner, industrial vacuum cleaners, cable protection, exhaust gas extraction
- Structure** TPO, black / jet black (similar RAL 9005), opaque, profile helix / solid profile helix
- Temperature** -50°C up to 60°C
- Properties** Innen glatter Profil-Vollkunststoffschlauch mit sehr geringem Strömungswiderstand, guter Rückstellkraft (trittfest) und sehr flexibel



| Inner Diameter (mm) | Outer Diameter (mm) | Bending Radius (mm) | Operating Pressure (bar) | Vacuum Max. (bar) | Weight (kg/m) | Article Number |
|---------------------|---------------------|---------------------|--------------------------|-------------------|---------------|----------------|
| 27 | 34,00 | 45 | 0,50 | 0,50 | 0,15500 | 4-2206-027-00 |
| 29 | 36,00 | 45 | 0,50 | 0,50 | 0,16500 | 4-2206-029-00 |
| 32 | 39,00 | 50 | 0,45 | 0,45 | 0,18500 | 4-2206-032-00 |
| 38 | 45,00 | 55 | 0,35 | 0,35 | 0,22000 | 4-2206-038-00 |
| 50 | 58,00 | 75 | 0,20 | 0,20 | 0,28950 | 4-2206-050-00 |