# PONDFLEXX

Flexible corrugated profile hose made of modified TPO, integrated cuffs, without spiral

**Applications** pond technology, filter systems, pool & whirlpool, water drain, waste water

**Structure** TPO, black, opaque

**Temperature** -30°C up to 60°C

**Properties** light weight, good flexibility, good ozone- & UV-resistance, hydrolysis & microbe resistant, weather proof, rot proof, floatable, cuff distance 1,5 m









made in Germany

| Inner Diameter (mm) | Outer Diameter (mm) | Wall Thickness (mm) | Bending Radius (mm) | Vacuum Max. (bar) | Weight (kg/m) | Article Number |
|---|---|---|---|---|---|---|
| 25 | 28,00 | 1,50 | 60 | 0,40 | 0,09000 | 5-8106-025-30 |
| 32 | 39,00 | 3,50 | 80 | 0,40 | 0,17000 | 5-8106-032-30 |
| 32 | 39,00 | 3,50 | 80 | 0,40 | 0,17000 | 5-8106-032-31 |
| 38 | 45,00 | 3,50 | 95 | 0,40 | 0,21500 | 5-8106-038-30 |
| 38 | 45,00 | 3,50 | 95 | 0,40 | 0,21500 | 5-8106-038-32 |



Ocono VACUFLEX GmbH | Hessenring 8-12 | 64546 Mörfelden-Walldorf | Germany | T +49 6105 93390 | vacuflex@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026