VACUFLEX® VSM-POOL

Smooth-bore, solid plastic hose with very low flow resistance



Applications swimming pool technology, vacuum cleaner, cleaning, pool & whirlpool, industrial vacuum cleaners

Structure TPO, uncolored, translucent, profile helix / solid profile helix

Temperature -50°C up to 60°C

Properties excellent flexibility, corrugated outside, smooth inside, crush-resistant, can be driven over, good resistance to compressed air containing mineral oil, good oil & petrol resistance, good ozone- & UV-resistance, hydrolysis & microbe resistant, rot proof, weather proof





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
32	40,50	80	0,50	0,50	0,21850	4-1100-032-01
38	48,00	95	0,40	0,40	0,25900	4-1100-038-01
50	61,00	120	0,25	0,25	0,33881	4-1100-050-01
51	62,00	122	0,25	0,25	0,34584	4-1100-051-01

Ocono VACUFLEX GmbH | Hessenring 8-12 | 64546 Mörfelden-Walldorf | Germany | T +49 6105 93390 | vacuflex@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.

Date: 24.11.2026