LIMBERFLEXX SE PU MHR

Highly flexible polyether-polyurethane hose with coated spring steel wire, abrasion-resistant, halogen-free



Applications cleaning, extraction systems, industrial vacuum cleaners, air supply, waste water

Structure Polyether-Polyurethane, black / jet black (similar RAL 9005), opaque, steel wire / spring steel wire / coated / PU

Temperature -40°C up to 90°C, short term up to 125°C

Properties excellent flexibility, excellent temperature resistance, very good low-temperature flexibility, good tensile strength, ultimate elongation, hydrolysis & microbe resistant, good ozone- & UV-resistance





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Length (m)	Article Number
32	36,00	32	0,60	1,80	0,40	0,17900	100	8-2806-032-00/999
38	42,00	38	0,60	1,80	0,40	0,20500	100	8-2806-038-00/999

Ocono VACUFLEX GmbH | Hessenring 8-12 | 64546 Mörfelden-Walldorf | Germany | T +49 6105 93390 | vacuflex@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026