TWINFLEXX PU (RUND)

Durable and flexible, double-walled TPU hose with an integrated PVC inner hose for steam cleaners and spray-extraction machines

Applications	cleaning, steam extraction, industrial vacuum cleaners, sprayers
Structure	Polyether-Polyurethane, black / jet black (similar RAL 9005), opaque, steel wire / spring steel wire / coated / PU
Temperature	-40°C up to 90°C, short term up to 125°C
Properties	very good flexibility, good low-temperature flexibility, very good abrasion resistance, very smooth inside, hydrolysis & microbe resistant, flex fatigue resistance > 200,000 cycles, flexibility factor min. 0.25
Optional	max. production length: 16 m; also available with an oval smooth hose







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
31	37,50	1,50	2,30	4,50	1,00	0,39600	5-9306-031-00

Ocono VACUFLEX GmbH | Hessenring 8-12 | 64546 Mörfelden-Walldorf | Germany | T +49 6105 93390 | vacuflex@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 23.11.2026