

VACUFLEX® PU 400 FR MHR ECO


Lightweight and highly flexible flame-retardant spiral hose made of polyether polyurethane

Applications extraction systems, wood dust extraction, extractions arms, air supply, air extraction

Structure TPU / Polyether-Polyurethane, uncolored, transparent, steel wire / spring steel wire / not coated / copper plated

Temperature -40°C up to 90°C, short term up to 125°C

Properties Sehr leichter und extrem flexibler PU-Schlauch mit großer Bruchdehnung und guter Zug- und Abriebfestigkeit, Weichmacherzusatzfrei, halogenfrei und cadmiumfrei, ECO friendly. Gemäß TRGS 727 und ATEX 2014/34 EU, bei beidseitiger Erdung der Spirale zur aspirativen und pneumatischen Förderung nicht brennbarer Stäube und Schüttgüter in Zone 22. Fördern von Gasen und Flüssigkeiten mit niedriger Leitfähigkeit in Zone 2.



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
32	36,00	0,40	36	0,60	0,25	0,14100	7-9000-032-00/998
35	39,00	0,40	39	0,60	0,25	0,13500	7-9000-035-00/998
38	42,00	0,40	42	0,60	0,25	0,14600	7-9000-038-00/998
40	44,00	0,40	44	0,60	0,25	0,17600	7-9000-040-00/998
42	46,00	0,40	46	0,60	0,25	0,18600	7-9000-042-00/998
45	49,00	0,40	49	0,60	0,25	0,19900	7-9000-045-00/998
48	52,00	0,40	52	0,60	0,25	0,21100	7-9000-048-00/998
50	54,00	0,40	54	0,60	0,25	0,22100	7-9000-050-00/998
51	55,00	0,40	51	0,50	0,20	0,22600	7-9000-051-00/998
55	59,00	0,40	55	0,50	0,20	0,24100	7-9000-055-00/998
60	64,00	0,40	60	0,50	0,20	0,26800	7-9000-060-00/998
65	69,00	0,40	65	0,40	0,15	0,28400	7-9000-065-00/998
70	74,00	0,40	70	0,40	0,15	0,33200	7-9000-070-00/998
75	79,00	0,40	75	0,40	0,15	0,35500	7-9000-075-00/998
76	80,00	0,40	76	0,40	0,15	0,36000	7-9000-076-00/998
80	84,00	0,40	80	0,30	0,10	0,34200	7-9000-080-00/998
83	87,00	0,40	83	0,30	0,10	0,39200	7-9000-083-00/998
90	94,00	0,40	90	0,30	0,10	0,42400	7-9000-090-00/998
100	105,00	0,40	100	0,30	0,10	0,44800	7-9000-100-00/998
102	107,00	0,40	102	0,25	0,08	0,45600	7-9000-102-00/998
110	115,00	0,40	110	0,25	0,08	0,49200	7-9000-110-00/998
120	125,00	0,40	120	0,25	0,08	0,53800	7-9000-120-00/998

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
125	130,00	0,40	125	0,25	0,08	0,55700	7-9000-125-00/998
127	132,00	0,40	127	0,25	0,08	0,56900	7-9000-127-00/998
130	135,00	0,40	130	0,25	0,08	0,58200	7-9000-130-00/998
140	145,00	0,40	140	0,25	0,08	0,62800	7-9000-140-00/998
150	155,00	0,40	150	0,25	0,08	0,66600	7-9000-150-00/998
152	157,00	0,40	152	0,25	0,08	0,67500	7-9000-152-00/998
160	165,00	0,40	160	0,15	0,05	0,72000	7-9000-160-00/998
175	180,00	0,40	175	0,15	0,05	0,77600	7-9000-175-00/998
180	185,00	0,40	180	0,15	0,05	0,81000	7-9000-180-00/998
200	206,00	0,40	200	0,15	0,05	0,94800	7-9000-200-00/998
203	209,00	0,40	203	0,15	0,05	0,98500	7-9000-203-00/998
225	231,00	0,40	225	0,15	0,05	1,04800	7-9000-225-00/998
250	256,00	0,40	250	0,10	0,02	1,18300	7-9000-250-00/998
280	286,00	0,40	280	0,10	0,02	1,30100	7-9000-280-00/998
300	306,00	0,40	300	0,10	0,02	1,50000	7-9000-300-00/998
350	356,00	0,40	350	0,10	0,02	1,74800	7-9000-350-00/998