

VACUFLEX® VC2 PU MHR

Very smooth inside full plastic hose made of Polyurethane

Applications	cable protection, conveying of abrasive media, conveying technology, granulate conveying, medical devices
Structure	TPU / Polyether-Polyurethane, black / jet black (similar RAL 9005), opaque, plastic spiral / rigid PVC
Temperature	-30°C up to 90°C
Properties	good flexibility, good abrasion resistance, corrugated outside, very smooth inside, good ozone- & UV-resistance, hydrolysis & microbe resistant, rot proof, weather proof



Inner Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
10	10	3,50	0,95	0,06000	3-6806-010-00/999
13	13	3,50	0,95	0,09500	3-6806-013-00/999
20	20	3,50	0,95	0,14800	3-6806-020-00/999
25	25	2,50	0,65	0,18900	3-6806-025-00/999
30	30	2,50	0,65	0,22600	3-6806-030-00/999
32	32	2,50	0,65	0,18000	3-6806-032-00/999
38	38	2,50	0,60	0,26600	3-6806-038-00/999
40	40	2,50	0,60	0,31000	3-6806-040-00/999
45	45	2,50	0,60	0,33700	3-6806-045-00/999
50	50	2,00	0,55	0,37700	3-6806-050-00/999
60	60	2,00	0,55	0,45200	3-6806-060-00/999